

Object Animation using deformable reference frames

Guillaume Bousquet

Under the direction of François Faure
Evasion team - LJK laboratory

INRIA Rhones-Alpes, 655 av. de l'Europe
38334 Saint Ismier Cedex France

May 26, 2008



Plan

1 Related work

- Mechanics of continuous material
- FEM, meshless deformations and mass-spring method
- Adaptive remeshing
- Skinning method

2 Contribution

- The deformable frames
- Attaching a surface
- Mass
- Elasticity response
- Deformations in higher dimensions
- Local deformations

3 Future work

Plan

- 1 Related work
 - Mechanics of continuous material
 - FEM, meshless deformations and mass-spring method
 - Adaptive remeshing
 - Skinning method
- 2 Contribution
 - The deformable frames
 - Attaching a surface
 - Mass
 - Elasticity response
 - Deformations in higher dimensions
 - Local deformations
- 3 Future work

Overview

Goal: find a model which interrelate the forces applied on a model and the resulting deformations.

Main idea:

- Sample the continuous middle.
- Define a displacement field.
- Integrate over space the equations of continuous material

Plan

1 Related work

- Mechanics of continuous material
- **FEM, meshless deformations and mass-spring method**
- Adaptive remeshing
- Skinning method

2 Contribution

- The deformable frames
- Attaching a surface
- Mass
- Elasticity response
- Deformations in higher dimensions
- Local deformations

3 Future work

Overview:

- Sample the continuous middle:

Finite elements: with a 2D or 3D mesh.

Meshless deformations: with a point cloud.

- Define a displacement field.

Finite elements: interpolated in each cell.

Meshless deformations: weighted sum of a radial basis function.

- Integrate over space the equations of continuous material

For all methods, derive the physical equations from:

- partial derivatives of the displacements field
-

Physical simulation:

	Pros	Cons
Finite elements	precision	mesh resolution
Meshless deformations	no topology \Rightarrow cutting, adaptivity	precision implementation
mass-spring method	implementation	precision edge mesh

Plan

1 Related work


- Mechanics of continuous material
- FEM, meshless deformations and mass-spring method
- **Adaptive remeshing**
- Skinning method

2 Contribution

- The deformable frames
- Attaching a surface
- Mass
- Elasticity response
- Deformations in higher dimensions
- Local deformations

3 Future work

[*Charms, Grinspun et al.* 2002] has dynamically added DOFs during the computation to obtain better results.



Plan

1 Related work

- Mechanics of continuous material
- FEM, meshless deformations and mass-spring method
- Adaptive remeshing
- **Skinning method**


2 Contribution

- The deformable frames
- Attaching a surface
- Mass
- Elasticity response
- Deformations in higher dimensions
- Local deformations

3 Future work

Principle:

The position of the skin (surface) is a linear combination of the bones (DOFs).



Weighting:

Problem on large bend and twist deformations.

Solution: other weights.

Ex: arclength, $1/d$, $1/d^2$, or as in [VGL, KunZhou et al. 2005]





Figure 2: Large twist deformation.



Plan

- 1 Related work
 - Mechanics of continuous material
 - FEM, meshless deformations and mass-spring method
 - Adaptive remeshing
 - Skinning method
- 2 **Contribution**
 - **The deformable frames**
 - Attaching a surface
 - Mass
 - Elasticity response
 - Deformations in higher dimensions
 - Local deformations
- 3 Future work

Kinematic primitive

New 12D DOF:

$$x = (\vec{t}, q, \vec{s}h, \vec{s}t)^T$$

$$v = (\dot{\vec{t}}, \Omega, \dot{\vec{s}h}, \dot{\vec{s}t})^T$$

$$f = (\vec{f}_t, \vec{f}_r, \vec{f}_{sh}, \vec{f}_{st})^T$$




Figure: movie of shear effect




Figure: movie of stretch effect

Plan

- 1 Related work
 - Mechanics of continuous material
 - FEM, meshless deformations and mass-spring method
 - Adaptive remeshing
 - Skinning method
- 2 **Contribution**
 - The deformable frames
 - **Attaching a surface**
 - Mass
 - Elasticity response
 - Deformations in higher dimensions
 - Local deformations
- 3 Future work

Displacement field:


$$\vec{p}_0 = \vec{t}_0 + B_{1/0} * \vec{p}_1$$

with $B_{1/0} = RE$.

R is a rotation matrix

and E contains the shear and stretch components.

$$E = \begin{pmatrix} 1 + e_{xx} & e_{xy} & e_{zx} \\ e_{xy} & 1 + e_{yy} & e_{yz} \\ e_{zx} & e_{yz} & 1 + e_{zz} \end{pmatrix}$$



Velocity of a point

Coord: $\vec{p}_0 = \vec{t}_0 + B_{1/0} * \vec{p}_1$

Vel : $\dot{\vec{p}}_0 = \dot{\vec{t}}_0 + \dot{B}_{1/0} * \vec{p}_1$

(with $\dot{B}_{1/0} = \dot{R}E + R\dot{E}$)

Displacement interpolation

matrix: $J = \frac{du}{dx}$

So,

$$\dot{\vec{p}}_0 = J(p) v_{DOF}$$

$$f_{DOF} = \sum J(p)^T \vec{f}_p$$

(according to virtual powers)




Figure: demo of surface collision

Plan

- 1 Related work
 - Mechanics of continuous material
 - FEM, meshless deformations and mass-spring method
 - Adaptive remeshing
 - Skinning method
- 2 **Contribution**
 - The deformable frames
 - Attaching a surface
 - **Mass**
 - Elasticity response
 - Deformations in higher dimensions
 - Local deformations
- 3 Future work

The mass matrix is used to compute accelerations.

According to Newton: $f_{[12 \times 1]} = m_{[12 \times 12]} a_{[12 \times 1]}$

And according to the mecanic of continuous middle: $M = \int \rho J J^T dv$

	$tr_{1 \times 3}$	$rot_{1 \times 3}$	$sh_{1 \times 3}$	$st_{1 \times 3}$
$tr_{3 \times 1}$ $rot_{3 \times 1}$ $sh_{3 \times 1}$ $st_{3 \times 1}$	$M_{12 \times 12}$			

Plan

- 1 Related work
 - Mechanics of continuous material
 - FEM, meshless deformations and mass-spring method
 - Adaptive remeshing
 - Skinning method
- 2 **Contribution**
 - The deformable frames
 - Attaching a surface
 - Mass
 - **Elasticity response**
 - Deformations in higher dimensions
 - Local deformations
- 3 Future work

We need a shear and stretch constraint to simulate the elasticity response on our deformable frames.

$$\begin{aligned}\dot{\vec{shear}} + &= -k_{\vec{shear}} * \vec{shear} \\ \dot{\vec{stretch}} + &= -k_{\vec{stretch}} * \vec{stretch}\end{aligned}$$




Figure: linear deformation demo

Plan

- 1 Related work
 - Mechanics of continuous material
 - FEM, meshless deformations and mass-spring method
 - Adaptive remeshing
 - Skinning method
- 2 **Contribution**
 - The deformable frames
 - Attaching a surface
 - Mass
 - Elasticity response
 - **Deformations in higher dimensions**
 - Local deformations
- 3 Future work

We have linear deformations, but we want more !
So, we create a spring to begin skinning with the DOFs.




Figure: video of spring without damping




Figure: video of spring with damping

Now, we are able to do a linear combinaison between the DOFs.




Figure: demo using skinning

Plan

- 1 Related work
 - Mechanics of continuous material
 - FEM, meshless deformations and mass-spring method
 - Adaptive remeshing
 - Skinning method
- 2 **Contribution**
 - The deformable frames
 - Attaching a surface
 - Mass
 - Elasticity response
 - Deformations in higher dimensions
 - **Local deformations**
- 3 Future work

unrealistic deformation \Rightarrow We need local deformations.
So, we create a contact manager.





Figure: video of local deformations

- Finish the contact manager
- Animation applications
- Results physically exact
- Other functionalities

Automatically remove DOF
Different influence radius

- Finish the contact manager
- **Animation applications**
- Results physically exact
- Other functionalities

Video games with skinning
Ragdoll effect



- Finish the contact manager
- Animation applications
- Results physically exact
- Other functionalities

For medical simulation.

Compute the M, J and K matrices based on the mesh geometry or volumetric images.

According to the mecanic of continuous middle:

$$M = \int \rho J J^T dv$$

$$K = \int B^T C B dv$$

- Finish the contact manager
- Animation applications
- Results physically exact
- Other functionalities

Cutting
Tearing

